

Liebert® GXT3, 10000 VA T Model

Reliable On-Line Protection In A Compact Tower Package

AC Power for
Business-Critical Continuity™



Flexibility:

- Automatic frequency detection
- User replaceable hot-swappable internal batteries
- Extended back up time with additional battery cabinets
- Liebert IntelliSlot™ communications port
- Includes Windows-based configuration program
- Built-in USB communications for use with Liebert MultiLink™ automated shutdown software
- Built-in closure signals
- Emergency power off (EPO)
- Parallelable up to three units

Higher Availability:

- Wider input voltage window minimizes battery use
- Internal automatic and manual bypass
- Self-diagnostics

Reduced Total Cost Of Ownership:

- Standard two-year warranty
- Compact footprint
- Batteries shielded from heat generating electronic components
- Battery cutoff voltage to prevent from overdischarge of batteries

Liebert GXT3 is designed to deliver higher power capacities for applications with limited floor space. This true on-line double conversion UPS system is available in two different 10000 VA versions featuring an integrated maintenance bypass, as well as optional extended battery back up time.

Liebert GXT3 T230 is the standard version free of integrated isolation transformer which can be configured as either 1/1 or 3/1, providing increased flexibility. The Liebert GXT3 range also offers the possibility of integrated full galvanic isolation with the Liebert GXT3 T220 which houses an output isolation transformer allowing it to be used at 110, 120 phase to neutral or 208, 220 phase to phase voltages, for dual input with phases shifted by 180 degrees.

Communications For Power Monitoring And Control

Liebert GXT3 offers a variety of communications options providing flexible monitoring and control capabilities.

Operation can be monitored using:

- Liebert IntelliSlot™ web card providing SNMP and web-based monitoring and control of the UPS
- Liebert MultiLink™ automated system shutdown software
- Liebert Nform™ monitoring system
- Third-party monitoring systems

Ideally suited for Mission-Critical Applications such as:

- LAN & WAN servers
- Network equipment
- IP telephony deployments
- Office telecommunications systems
- ISDN & frame relay applications
- Test and diagnostic equipment
- Micro Processor-controlled equipment
- Finance applications



Liebert GXT3
10000 VA Tower

0.9 PF
More Power
Available!


EMERSON
Network Power

Liebert® GXT3, 10000 VA T Model

Specifications

Model Number	GXT3-10000T230	GXT3-10000T220
Power Rating	10000 VA/9000 W	
Dimensions, W x D x H - mm	300 x 675 x 800 / 426 x 866 x 1062	
Unit / Shipping	300 x 675 x 800 / 426 x 866 x 1062	
Weight - kg	105	
Unit	105	140
Input AC Parameters		
Voltage Range Without Battery Operation	176-280VAC (for 1/1) 304-485VAC (for 3/1)	100 - 185 ±5VAC (for 1/1)
Frequency Range	50 - 60Hz autoselection	
Input Socket	terminal block	
Output Sockets	terminal block	
Voltage	220/230/240VAC	208VAC
Waveform	Sinewave	
Battery Parameters		
Type	HR 1234W F12	CSB HR1234R or Panasonic UP-RW1245
Quantity x Voltage	20 x 12V	
Recharge Time	3 hours to 90% capacity after full discharge with 100% load (Internal Batteries Only)	
Environmental		
Operating Temperature	0 to 30 °C with 0.9 PF 30 to 40 °C with 0.8 PF	
Storage Temperature	- 15 to 50 °C	
Relative Humidity	0%RH to 95%RH, non-condensing	
Operating Altitude	Up to 1000m	
Audible Noise	< 55 dBA, at 1 meter from the rear < 50 dBA, at 1 meter from the front or sides	
Standards and Certifications	CE	UL 1778, cUL
RFI/EMI	IEC/EN/AS 62040-2 2nd Ed (Cat 2 – Table 6)	FCC Part 15, Subpart B, Class A
Surge Immunity	EN61000-4-5, Level 3, Criteria A	IEC/EN 61000-4-5, ANSI C62.41 (for North America)
Transportation	ISTA Procedure 1A	ISTA Procedure 1B

Liebert® GXT3 Battery Cabinet Specifications

Model Number	GXT3-240TBATT CE
Dimensions, W x D x H - mm	300 x 675 x 800 / 426 x 866 x 1062
Unit / Shipping	300 x 675 x 800 / 426 x 866 x 1062
Weight - kg	110/140
Unit / Shipping	110/140
Batteries	
Type	Valve-regulated, non-spillable, lead acid
Quantity x Voltage	2 x 20 x 12V
Environmental	
Operating / Storage Temperature, °C	0 to 40/-15 to 40
Relative Humidity	0% to 95%, non-condensing
Maximum Operating Altitude	Up to 10000m (40°C)
Standards and Certifications	
Safety / Emissions	CE
Transportation	ISTA Procedure 1A

Locations

Emerson Network Power

Via Leonardo Da Vinci 16/18
Zona Industriale Tognana
35028 Piove di Sacco (PD) Italy
Tel: +39 049 9719 111
Fax: +39 049 5841 257
marketing.emea@emersonnetworkpower.com

Via Fornace, 30

40023 Castel Guelfo (BO) Italy

Tel: +39 0542 632 111

Fax: +39 0542 632 120

enquiries.chloride@emerson.com

United States

1050 Dearborn Drive

P.O. Box 29186

Columbus, OH 43229

Tel: +1 614 8880246

Asia

7/F, Dah Sing Financial Centre

108 Gloucester Road, Wanchai

Hong Kong

Tel: +852 2572220

Fax: +852 28029250



Tech Support

Always On! Our Commitment to your daily Business, provided by our World Wide multi language Tech Support.

Toll-free **0080011554499**

Toll **+39 02 98250222**

liebert.upstech@emerson.com

While every precaution has been taken to ensure the accuracy and completeness of this literature, Liebert Corporation assumes no responsibility and disclaims all liability for damages resulting from use of this information or for any errors or omissions. ©2011 Liebert Corporation

All rights reserved throughout the world. Specifications subject to change without notice.

GXT3T-FLY-EN-1010-03
MKA4LOUKGXT3T Rev.1-07/2011

Emerson Network Power™

The global leader in enabling Business-Critical Continuity™.


AC Power

- Connectivity
- DC Power
- Embedded Computing
- Embedded Power
- Infrastructure Management & Monitoring
- Outside Plant
- Power Switching & Controls
- Precision Cooling
- Racks & Integrated Cabinets
- Services
- Surge Protection

Emerson Network Power.com

Emerson, Business-Critical Continuity™ and Emerson Network Power are trademarks of Emerson Electric Co. or one of its affiliated companies. ©2011 Emerson Electric Co.

Liebert GXT3-10000T230



Liebert GXT3-10000T220

